



- Slip retarding and wear resistant polish
- Self polishing – enriches tile colour and structure
- Easy maintenance – dirt-repellent effect

Product

Metallized acrylic-based maintenance agent.
Applicable on most hard floorings.
Not suitable for wet rooms and for exterior use.

Coverage

1 – 1½ litres per 100 m² coating

Packaging

1 litre and 2½ litres container

Applications

Produces a satin smooth, glossy surface protection on e.g. unglazed ceramic tiles, quarry tiles, unpolished marble, slates, and natural stone.
Ideal for sealing of pores on absorbent tiles prior to grouting to ease subsequent removal of cement film.
Alfix Floor Polish can be dissolved and removed with Alfix Deep Cleaner.

Surface preparation

Clean the surface using Alfix Deep Cleaner.

Instructions for use

Initial treatment:

Apply 1 – 3 coatings of concentrated Alfix Floor Polish to the dry, clean floor in parallel lengths using damp cloth or sponge. Leave the surface to dry between each coating. Thin applications produce the best final result.

Cleaning/maintenance:

Polished surfaces can be washed/maintained with Alfix Floor Polish using ½ – 1 dl per 10 litres of water. Alternatively, Alfix Floor Cleaner can be used.

Cleaning

Polish can be removed with Alfix Deep Cleaner.

Technical enquiries

Product info on:

- Alfix Deep Cleaner
- Alfix Floor Cleaner

Product health and safety data /COSH

For further information, please consult our Technical Services Dept.
For latest update of this product info, visit www.alfix.com.

Technical data

pH-value approx. 9.0

Shelf life Protect from frost

Min. 12 months at +20°C

