



- · Cleaning and maintenance in one operation
- Enriches tile colour and structure
- · Rapid pore filler smoothing rough surfaces
- · Produces anti-static slip-retarding protection film

Product

Combined cleaning and maintenance agent. Contains natural wax.

Suitable for use on all washable floorings.

Coverage

Routine cleaning: 1/4 - 1/2 dl per 10 litres of water.

Packaging

1 litre container

Applications

For regular cleaning and maintenance of e.g. terracotta, unglazed ceramic tiles, marble, and natural stone Further for pore filling of absorbent surfaces.

Instructions for use

Pore filling:

Dilute Alfix Floor Cleaner with water 1:5 - 1:10. Apply and wash well into the surface.

Do not rinse subsequently with clean water.

Once the surface is dry, a sheen or a semi-gloss appearance can be obtained if dry polishing.

Cleaning/maintenance:

Add Alfix Floor Cleaner to the washing water.

Regular dosage is ¼ - ½ dl per 10 litres of water.

Cleaning

Film can be removed with Alfix Deep Cleaner.

Technical enquiries

Product info on:

Alfix Deep Cleaner

Product health and safety data /COSH

For further information, please consult our Technical Services Dept. For latest update of this product info, visit www.alfix.com.

Technical data

pH-value approx. 8.5 Shelf life Protect from frost Min. 12 months at +20°C

